

Product presentation

**LIQUI
MOLY
MARINE**

Marine High Performance Gear Oil 85W-90



Special high-performance gear lube for the maritime sector. With unique package of additives that guarantees outstanding wear protection even in the case of contamination with water. Stable under extreme pressures even under high stresses and at high speeds. Its outstanding corrosion protection and very good oxidation resistance make it perfect for maritime applications. Prevents oil sludge and deposits even under higher operating temperatures.

Meets the requirements of common transmission manufacturers like Honda, Yamaha, Mercury etc. For Mercury outboard motors as of 75 hp output as well as MerCruiser Z-drives. Can be used as a replacement for a high-performance gear lube with viscosity SAE 90.

Properties

- outstanding corrosion protection
- high pressure-absorption capability
- excellent viscosity/temperature properties
- stable to ageing and stable viscosity
- excellent high-pressure and wear protection properties
- guarantees lubrication also with a certain amount of water in the tank

Part no.	Product	Content	Language	PU
25078	Marine High Performance Gear Oil 85W-90	1 l	D-F-I-E-GR	6
25079	Marine High Performance Gear Oil 85W-90	1 l	GB-DK-N-FIN-S-RUS	6
25080	Marine High Performance Gear Oil 85W-90	20 l	D-GB	1
25081	Marine High Performance Gear Oil 85W-90	60 l	D-GB	1

Note the boat and transmission manufacturers' operating instructions. Can not be mixed with oils of other specifications.

Tip

Our Marine High Performance Gear Oil 85W-90 was developed to meet the special requirements of marine gear boxes like having a better water emulsion performance to avoid the forming of a water layer which could cause corrosion.

Comparison

Multi-grade oil e.g. 75...-85W-90

- + rapid oil penetration at cold start
- + less wear
- + premium additive package for modern gear box generations
- + high viscosity index for a wide temperature range

Single-grade oil e.g. SAE 90

- slow oil penetration after cold start and low outside temperatures
- normally simple gear oil formulations



LIQUI MOLY GmbH
Jerg-Wieland-Straße 4
89081 Ulm
GERMANY

Phone: +49 731 1420-0
Fax: +49 731 1420-75
E-Mail: info@liqui-moly.com
www.liqui-moly.com

Technical Support:
+49 731 1420-871
No liability for misprints.
Subject to technical modifications.

508991801